VULCAN X

Vehicle Mount Computer

Selling Features



Always on rugged

Contents

- 01 Introduction
- 02 Outlook
- 03 Features Highlight
- 04 Applications



VULCAN X 10.4"

Confidential

Target Segment



Agriculture



Warehouse forklift



Cold Chain Logistics



Mining Truck



Waste management trucks



Port cranes

Confidential

Specifications

System

- Intel Core i5-8365UE 1.6GHz
 Intel Celeron 4305UE 2GHz (optional)
- 4GB DDR4 SODIMM, expandable to 32GB
- M.2 2280 SSD
- Built-in 6-axis motion sensor, built-in 2 speakers

Display

- 10.4" XGA TFT LCD with LED backlight (1024 x 768)
- · 1200 nits brightness supports auto-dimming
- 5-wire resistive touch supports defrost/ defog function
- PCT touchscreen supports glove and rain mode (by request)

Communication

- Wi-Fi 802.11 a/b/g/n/ac/v/r/k
- Bluetooth V5.0
- Optional 4G LTE / HSPA+ / GPRS or 5G
- Optional GNSS (GPS/Galileo/GLONASS/BeiDou/QZSS)

Function Button

- Programmable button x 7, brightness adjustment x 2, volume adjustment x 2, display on/off x 1
- Optional defrost/ defog button x 1

I/O Interface

- RS-232 with power supported x 1
- RS-232(TX,RX)/422/485 x 1, RS-232(TX,RX) x 2, RS-485 x 2
- Gigabit Ethernet x 2
- USB 3.1 x 1, USB 2.0 x2, USB 3.1 type C x 1 (DP Alt Mode supported)
- Micro SD slot x 1, Micro SIM slot x 2
- Optional CAN bus 2.0B x 2 or SAE J1939 x 1
- DI x 2, DO x 2
- Mic in x 2, Line out (L/R) x 1
- · Optional video input

Power Management

- 9~60 VDC input
- Ignition sense with delay on/off setting
- Wake on RTC
- Internal backup battery for graceful shutdown

Durability


- IP66, MIL-STD-810H, IEC 60721-3-5 class 5M3
- Operating temperature: -30°C to 55°C


Dimensions & Weight

• 276 x 234 x 57 (mm)



ID Diagram & Dimensions






• VULCAN $X = 276 \times 234 \times 57 \text{ (mm)}$; 3.2 kg

Front View



✓ You can configure the programmable buttons via DashON to different commands or keyboard shortcuts to better fit your work style

Rear View



I/O Interfaces






Robust Construction

- ♦ All-around IP66 protection: : IEC 60529
- **♦** A wide operating temperature range from -30°C to 55°C
- Shock and Vibration Resistance
 - ♦ MIL-STD-810H 514.8 procedure
 - US highway trucks (Figure 514.8C-2 Category 4)
 - composite two-wheeled trailers (Figure 514.8C-4 Category 4)
 - composite wheeled vehicles (Figure 514.8C-6 Category 4)
 - ♦ MIL-STD-810H 516.8 procedure
 - Operating: Procedure 1 Functional Shock
 - Non-Operating: Procedure V Crash Hazard Shock
 - ◆ IEC 60721-3-5 Class 5M3





Robust Construction

Salt fog corrosion resistance

- Featuring corrosion resistant coatings and screws
- Salt fog testing is performed in accordance with MIL-STD-810H METHOD 509.7 SALT FOG

Metal and secured connectors

- Against oil contamination, UV, vibrations, shocks, and expanded temperature range
- Secured M12 connectors for serial, digital I/O, USB and Ethernet
- M12 connectors with different coding to avoid mis-plug in the cable





Superb Visibility



The high brightness (1200 nits) display with auto-dimming feature enhances the visibility in any ambient light conditions



Confidential 13

Defroster Function

With optional screen defog and defroster, the applications can be extended from outdoor to cold storage environments.





Press defog/ defroster button



5G Ready

Reserve an expansion module and antennas for 5G



- Ultra-reliable low latency communications
- Enhanced mobile broadband
- Advantages in monitoring, tracking and smart surveillance applications

SMA antenna connectors



High Performance WiFi Network

- ◆ Dual-band Support with IEEE 802.11 a/b/g/n/ac
- ◆ Fast roaming support (802.11k/v/r)


VULCAN X can stay seamlessly connected throughout the network coverage area and roam smoothly among the Aps.



Fast Roaming

Smart Power Management

 Vehicle-grade power protection against sudden surges, noise filtering, overvoltage/ lower voltage and overcurrent protection



♦ 9 ~ 60 VDC wide range power input


- Ignition sense and delay on/off setting support
- A backup battery for safe shutdown and data saving while the sudden power loss



Backup battery under the cover


Second Display Available

- ◆ Easy to connect second display by a simple one cable : USB Type-C DisplayPort Alt Mode
- Support two display mode extended mode or clone mode



Extended mode







Clone mode

Flexible I/O Orientation


The varied I/O orientation design reserved to match different application scenarios.





Tailored Accessories







Warehouse Management

Application:

Forklift for outdoor/ cold storage

Requirement:

- ✓ Anti-Vibration/Shock
- ✓ 24/48V wide range power input
- ✓ Bluetooth to connect the barcode scanner
- ✓ Wi-Fi fast roaming for real-time warehouse management
- ✓ Defrost/ defog for cold chain



Port and Terminal

Application:

Container handling forklift and material handlers

Requirement:

- ✓ Anti-Vibration/Shock
- ✓ IP66 grade waterproof for outdoor
- ✓ Anti-salt fog corrosion resistance
- ✓ Wi-Fi for real-time terminal management
- ✓ 4G/5G...





Waste Management

Application:

Garbage pick-up, route management, monitoring

Requirement:

- ✓ GPS for route management
- ✓ WWAN network to cloud database
- ✓ Backup battery
- ✓ Rich I/O for RFID/ Weight scaler/ Printer
- ✓ Rear side, lateral side camera for safety and behavior record

