# VX-601 Rugged Vehicle Terminal

# **Selling Features**



Always on rugged

## **Contents**

- 01 Specifications
- 02 Outlook
- **Features & Peripherals**
- 04 Applications



VX-601 12.1"

# **Specifications**

#### **System**

- Intel Core i5-6300U 2.4GHz, optional Intel Celeron 3955U 2GHz
- · 4 GB DDR3L, expandable to 32 GB
- · M.2 2280 SSD, SD slot; dual speaker

#### **Display**

- 12.1", 1024 x 768, 700 nits / 1200 nits, supports autodimming
- · Resistive touch, optional defroster, PCT by request

#### Communication

- Gigabit Ethernet (RJ45)
- · WiFi / Bluetooth
- · Optional GNSS, 4G LTE / GPRS / HSPA+

#### **Function Button**

 Programmable button x 9, brightness adjustment x 2, volume adjustment x 2, display on/off x 1, optional defrost/ defog button x 1

#### I/O Interface

- RS-232 w/ power supported x 1, RS-232/422/485 x 1
- USB 2.0 x1, USB 3.0 / 2.0 x 1
- DI x 2, DO x 2
- CAN bus (SAE J1939 / OBD II\* supported) x 1
- · Audio headset jack x 1
- · Optional video input x 4

#### **Power Management**

- 9~60 VDC; backup battery
- · Ignition sense w/ delay on/off setting
- · Wake on RTC

#### **Durability**

- IEC 60529 IP66, MIL-STD-810G, IEC 60721-3-5 class 5M3
- Operating temperature : -30°C to 55°C

#### **Dimensions & Weight**

• 325 x 280 x 67.3 (mm); 4.83 kg

\* By request




## **Front View**




#### **Friendly Programmable Keys**

✓ You can configure the programmable buttons via DashON to different commands or keyboard shortcuts to better fit your work style

## **Rear View**



## **Bottom View**





# Features & Peripherals

# **Superb Visibility**




Brightness adjustable and auto-dimming



1200 nits high brightness supports auto-dimming


#### **♦** Anti-reflection touchscreen





## **Defroster Function**

With optional screen defroster, the applications can be extended from outdoor to cold storage environments.





Press defroster button



## **Durable Features**



✓ IEC 60529 IP66



✓ MIL-STD-810G

- Vibration (operating)
  Method 514.7 c2/c3/c4;
  IEC 60721-3-5 Class 5M3
- Shock (operating)40G at 11ms Terminal / Sawtooth
- Salt fog Change1, Method 509.6



**✓** Operating temp.

-30°C to 55°C (-22°F to 131°F)

 Purpose-built for the most challenging environments



**Waterproof Connectors** 

# **Smart Power Management**

- ◆ Wide power input to fulfill diversified vehicle application requirements
  - 12/24/48 VDC nominal (voltage range: 9 to 60 VDC)
- Ignition sense support with delay on/off setting
- Hand-rotate connector prevents power cord loosening








## **Smart Power Management**

## Built-in battery pack as UPS

- ✓ UPS to support 1.5hours working time
- Prevent damage from suddenly power loss via UPS battery
- ✓ Power design compliant with ISO-7637-2

REMARK

Battery discharge function will be automatically disabled while operation temperature is over 45°C based on battery protection scheme.



## **Seamless Communications**

#### **♦** Gigabit Wi-Fi

Intel 802.11ac Wi-Fi solution support both 2.4 GHz and 5 GHz bands

#### Bluetooth

Bluetooth 4.0 standard including Bluetooth 3.0 High Speed Bluetooth 4.0 Low Energy (BLE)

#### Optional GPS

GPS / QZSS or GLONASS

#### Optional WWAN

Via internal mini Card





# **Optional External antennas**:

WLAN / Bluetooth/ WWAN / GPS

## **Dedicated Software**

## DashON – System utility for device configuration

✓ DashON for easily setup the device for test and verification



✓ The completely SDK for quick application development


## Over the air update

- ✓ Remote update the utility and application
- ✓ Over the air update is to save time and resource in field



## Accessories







# **Warehouse Management**

## **Application:**

Forklift for outdoor/indoor

#### **Requirement:**

- ✓ Anti-Vibration/Shock
- ✓ IP66 grade waterproof solution
- ✓ 24/48V wide range power input
- ✓ Bluetooth to connect the barcode scanner
- ✓ Wi-Fi for real-time warehouse management



# **Harbor Freight**

## **Application:**

Container handling forklift and material handlers

#### **Requirement:**

- ✓ Anti-Vibration/Shock
- ✓ IP66 grade waterproof for outdoor
- ✓ 24/48V wide range power input
- ✓ Wi-Fi for real-time harbor management





# **Waste Management**

## **Application:**

Garbage pick-up, Route Management, Monitoring

## Requirement:

- ✓ GPS for route management
- √ 3.5G link to cloud database
- ✓ Backup battery kit
- ✓ Rear side, lateral side camera for safety and behavior record

